

## CLAIMS

Please cancel claims 1-3 without prejudice.

Please add the following new claims to the application:

4. A method for optimizing a network's configuration, comprising the steps of:

collecting pilot strength measurements for each base station included in said network;

saving said pilot strength measurements in a database, wherein said pilot strength measurements are saved regardless of the measurement value;

requesting a majority of said saved pilot strength measurements from said database;

compiling said pilot strength measurements for said each base station; and

modifying the transmission characteristics of said each base station in accordance with said compiled pilot strength measurements.

5. The method in accordance with claim 4, further comprising the step of using said compiled pilot strength measurements to simulate a cellular network.

6. The method in accordance with claim 4, wherein compiling said pilot strength measurements comprises the steps of:

determining an average energy for said pilot strength measurements for said each base station;

determining a maximum energy for a one of said pilot strength measurements for said each base station; and

determining a minimum energy for a one of said pilot strength measurements for said each base station.

7. The method in accordance with claim 6, further comprising  
the steps of:

analyzing the data compiled for said each base station to determine  
if said data indicates that a reliable communication between a mobile  
station and said each base station may be maintained;

if a reliable communication with said mobile station cannot be  
maintained by at least one of said each base station, then:

determining if said at least one of said each base station is in  
a neighbor list of said mobile station; and

communicating to said mobile station to remove said at least one of  
said each base station from said neighbor list.

8. The method in accordance with claim 4, wherein modifying  
the transmission characteristics of said at least one base station comprises  
changing the location of said at least one base station.

9. The method in accordance with claim 4, wherein modifying  
the transmission characteristics of said at least one base station comprises  
adjusting the spatial characteristics of an antenna used to transmit a signal  
from said each base station.

10. A method to optimize a network's configuration, comprising  
the steps of:

setting a set of parameters of a cellular network;

operating said cellular network for a predetermined interval;

measuring strengths of pilot signals received at a mobile station  
and caused by said operating;

communicating a pilot signal strength message from said mobile  
station to another station regardless of the strength of pilot;

saving data from said received pilot signal strength messages  
during said predetermined interval, said messages collected and saved  
regardless of said pilot signal strength; and

revising said set of parameters in accordance with said data from  
received pilot strength measurement messages.